

Masahiro TAKIZAWA et al., S.N. 10/511,964  
Page 2

RECEIVED  
CENTRAL FAX CENTER  
SEP 27 2006  
Ex. 1141/73200

### Listing of Claims

The following listing of claims will replace all prior versions, and listings, of claims in the subject application:

1. (currently amended) A magnetic resonance imaging apparatus comprising:  
a plurality of receiving coils for receiving a magnetic resonance signal generated from an object to be examined;  
~~sensitivity image data acquiring means for acquiring sensitivity image data by~~  
~~executing a first pulse sequence using the plural receiving coils from a plurality of slice~~  
~~positions separated from each other at intervals on the object;~~  
means for acquiring examination image data of each of the plural receiving coils from ~~the plural~~ a plurality of slice positions on the object sequentially adjoining on the object by executing a ~~second~~ first pulse sequence using the plural receiving coils while a phase encoding matrix in a k space is thinned out; ~~and~~  
artifact removing means for ~~generating sensitivity distribution data of the plural~~  
~~receiving coils on the slice positions of the examination image data on the basis of the plural~~  
~~sensitivity image data and removing an aliasing artifact in the examination image using the~~  
~~generated sensitivity distribution data of the receiving coils; and~~  
sensitivity image data acquiring means which acquires sensitivity image data by  
executing a second pulse sequence using the plural receiving coils from first and second slice  
positions, which have at least one unacquired slice position therebetween, of the plural slice  
positions on the object,  
wherein ~~an unmeasured sensitivity image of each receiving coil is calculated with a~~

Masahiro TAKIZAWA et al., S.N. 10/511,964  
Page 3

Dkt. 1141/73200

slice interpolation before the sensitivity distribution of each receiving coil is calculated the artifact removing means calculates the sensitivity image data of the receiving coils of the at least one unacquired slice position with a slice interpolation using the sensitivity image data of the first and the second slice positions, and generates the sensitivity distribution data of the plural receiving coils on the slice positions of the examination image data on the basis of the plural sensitivity image data.

2. (original) A magnetic resonance imaging apparatus according to claim 1, wherein the plural receiving coils include a receiving coil having a substantially uniform sensitivity distribution and a multiple receiving coil having a plurality of receiving coils.

3. (original) A magnetic resonance imaging apparatus according to claim 2, wherein the receiving coil having a substantially uniform sensitivity distribution is a coil which is also used for transmitting an RF pulse.

4. (previously presented) A magnetic resonance imaging apparatus according to claim 1, wherein  $n < m$  where the number of slices of sensitivity image data of the plural receiving coils is  $n$  and the number of slices of the examination image data is  $m$ .

5. (original) A magnetic resonance imaging apparatus according to claim 1, wherein the plural sensitivity image data are acquired with a multi-slice pulse sequence.

6. (original) A magnetic resonance imaging apparatus according to claim 1, wherein

Masahiro TAKIZAWA et al., S.N. 10/511,964  
Page 4

Dkt. 1141/73200

the sensitivity image data acquiring means measures an NMR signal of each of the plural receiving coils only in a low-frequency region of the k space having a predetermined phase encoding matrix.

7. (original) A magnetic resonance imaging apparatus according to claim 6, wherein the low-frequency region of the k space measured by the sensitivity image data acquiring means is the central portion in phase encoding direction of the k space and about one-fourth size of the whole phase encode matrix.

8. (original) A magnetic resonance imaging apparatus according to claim 2, wherein the examination image data acquiring means measures the NMR signal while thinning out every N steps in the phase encoding matrix of the k space of each receiving coil, where the number of receiving coils forming the multiple receiving coils is N.

9. (previously presented) A magnetic resonance imaging apparatus according to claim 1, wherein one or more sensitivity images of the multiple receiving coils corresponding to the slice positions of the examination image which is not yet measured are calculated with an interpolation calculation using the measured sensitivity distribution data.

10. (original) A magnetic resonance imaging apparatus according to claim 2, wherein the sensitivity distribution of each receiving coil of the multiple receiving coils is calculated by dividing the sensitivity image of each receiving coil by the sensitivity image obtained by the receiving coil having a substantially uniform sensitivity distribution.

Masahiro TAKIZAWA et al., S.N. 10/511,964  
Page 5

Dkt. 1141/73200

Claims 11-12 (canceled).

13. (original) A magnetic resonance imaging apparatus according to claim 1, wherein the number of the plural receiving coils is two.

14. (original) A magnetic resonance imaging apparatus according to claim 1, wherein the number of the plural receiving coil is three or more, those receiving coils are combined into a plurality of receiving coil group, and sensitivity distribution data are combined at each receiving coil group.

15. (currently amended) A magnetic resonance imaging apparatus comprising:  
a plurality of receiving coils for receiving an NMR signal generated from an object to be examined;

~~sensitivity image data acquiring means for acquiring sensitivity image data including an NMR signal of a low frequency region of a k space with each of the plural receiving coils from a plurality of slice positions separated from each other on the object by executing a first pulse sequence using the receiving coils;~~

means for acquiring an examination image data with each of the plural receiving coils from the plural a plurality of slice positions on the object sequentially adjoining on the object by executing a second first pulse sequence using the plural receiving coils where a phase encoding matrix of the k space is thinned out;

~~means for generating a sensitivity image data of each of the plural receiving coils on~~

Masahiro TAKIZAWA et al., S.N. 10/511,964  
Page 6

Dkt. 1141/73200

~~slice positions of the examination image data with an interpolation on the basis of the plural sensitivity image data and generating a sensitivity distribution of the plural receiving coils from thus generated sensitivity image data of receiving coil and the above plural sensitivity image data;~~

means for forming a determinant from [[the]] sensitivity distribution of the plural receiving coils and the examination image data of each of the receiving coils; and

artifact removing means for removing an aliasing artifact in the examination image by performing an inverse matrix calculation of the determinant; and

sensitivity image data acquiring means which acquires sensitivity image data by executing a second pulse sequence using the plural receiving coils from first and second slice positions, which have at least one unacquired slice position therebetween, of the plural slice positions on the object,

~~wherein an unmeasured sensitivity image of each receiving coil is calculated with a slice interpolation before the sensitivity distribution of each receiving coil is calculated the~~  
sensitivity image data of the receiving coils of the at least one unacquired slice position is calculated with a slice interpolation using the sensitivity image data of the first and the second slice positions, and the sensitivity distribution of the plural receiving coils on the slice positions of the examination image data is determined on the basis of the plural sensitivity image data.

16. (currently amended) A magnetic resonance imaging apparatus comprising;  
a plurality of receiving coils for receiving a nuclear magnetic resonance signal generated from an object to be examined;

Masahiro TAKIZAWA et al., S.N. 10/511,964  
Page 7

Dkt. 1141/73200

~~sensitivity image data acquiring means for acquiring sensitivity image data of each of the plural receiving coils on a plurality of slice positions separated from each other on the object by executing a first pulse sequence using the receiving coils;~~

~~sensitivity distribution data acquiring means for generating sensitivity image data of a substantially uniform sensitivity distribution by combining the sensitivity image data acquired by the plural receiving coils and calculating sensitivity distribution data of each receiving coil from thus combined sensitivity image data and the sensitivity image data of each receiving coil;~~

~~means for acquiring examination image data from the plural a plurality of slice positions on the object sequentially adjoining on the object by executing a second first pulse sequence using the receiving coils while a phase encoding matrix of the k space is thinned out;~~

sensitivity image data acquiring means which acquires sensitivity image data by executing a second pulse sequence using the plural receiving coils from first and second slice positions, which have at least one unacquired slice position therebetween, of the plural slice positions on the object; and

~~artifact removing means for removing an aliasing artifact in the examination image using [[the]] sensitivity distribution data of each receiving coil,~~

wherein an unmeasured sensitivity image of each receiving coil is calculated with a slice interpolation before the sensitivity distribution of each receiving coil is calculated the sensitivity image data of the receiving coils of the at least one unacquired slice position is calculated with a slice interpolation using the sensitivity image data of the first and the second slice positions, and the sensitivity distribution data of the plural receiving coils on the slice

Masahiro TAKIZAWA et al., S.N. 10/511,964  
Page 8

Dkt. 1141/73200

positions of the examination image data is generated on the basis of the plural sensitivity image data.

17. (currently amended) A magnetic resonance imaging method comprising:  
receiving a magnetic resonance signal generated from an object to be examined;  
~~acquiring sensitivity image data by executing a first pulse sequence using the plural receiving coils from a plurality of slice positions separated from each other at intervals on the object;~~

acquiring examination image data of each of the plural receiving coils from the plural  
a plurality of slice positions sequentially adjoining on the object by executing a second first  
pulse sequence using the plural receiving coils while a phase encoding matrix in a k space is  
thinned out;

acquiring sensitivity image data by executing a second pulse sequence using the plural receiving coils from first and second slice positions, which have at least one unacquired slice position therebetween, of the plural slice positions on the object, the sensitivity image data of the receiving coils of the at least one unacquired slice position being calculated with a slice interpolation using the sensitivity image data of the first and the second slice positions;

generating sensitivity distribution data of the plural receiving coils on the slice  
positions of the examination image data on the basis of the plural sensitivity image data; and

removing an aliasing artifact in the examination image using ~~thus generated the~~  
sensitivity distribution data of the receiving coils, ~~and calculating an unmeasured sensitivity image of each receiving coil with a slice interpolation before the sensitivity distribution of each receiving coil is calculated.~~

Masahiro TAKIZAWA et al., S.N. 10/511,964  
Page 9

Dkt. 1141/73200

18. (previously presented) The method of claim 17, wherein  $n < m$  where the number of sensitivity image data of the plural receiving coils is  $n$  and the number of the examination image data is  $m$ .

19. (previously presented) The method of claim 17, further comprising calculating one or more sensitivity images of the multiple receiving coils corresponding to the slice positions of the examination image which is not yet measured with an interpolation calculation using the measured sensitivity distribution data.